



US009408470B2

(12) **United States Patent
Smith**

(10) **Patent No.: US 9,408,470 B2**
(45) **Date of Patent: *Aug. 9, 2016**

(54) **METHOD OF IMPROVING SEAT COMFORT,
SEAT AND CUSHION SET ACCORDING TO
THE SAME**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Willem Smith & Company, LLC,**
Fairfax, VA (US)

428,819 A 5/1890 Stace
2,153,155 A * 4/1939 Page B60N 2/2209
297/331

(72) Inventor: **John W. Smith,** Great Falls, VA (US)

2,734,556 A 2/1956 Hebrank
2,765,480 A 10/1956 Mueller
3,019,051 A 1/1962 Nugent
3,279,849 A 10/1966 Radke et al.
3,602,548 A 8/1971 Grams
3,747,977 A 7/1973 Rowland
4,036,524 A 7/1977 Takamatsu
4,159,146 A 6/1979 Braconnier et al.
4,179,158 A 12/1979 Flaum et al.
4,190,918 A 3/1980 Harvell

(73) Assignee: **Willem Smith & Company, LLC,**
Fairfax, VA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 9 days.

This patent is subject to a terminal dis-
claimer.

(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/741,983**

GB 1033154 6/1966

(22) Filed: **Jun. 17, 2015**

Primary Examiner — Timothy J Brindley

(65) **Prior Publication Data**

US 2016/0183684 A1 Jun. 30, 2016

(74) *Attorney, Agent, or Firm* — Womble Carlyle Sandridge
& Rice, LLP

Related U.S. Application Data

(63) Continuation of application No. 14/587,943, filed on
Dec. 31, 2014, now Pat. No. 9,066,594.

(51) **Int. Cl.**

A47C 4/02 (2006.01)

A47C 7/02 (2006.01)

A47C 7/42 (2006.01)

(52) **U.S. Cl.**

CPC . **A47C 4/02** (2013.01); **A47C 7/021** (2013.01);
A47C 7/42 (2013.01)

(58) **Field of Classification Search**

CPC **A47C 7/42**; **A47C 7/425**; **A47C 4/028**

USPC 297/440.15, 452.11

See application file for complete search history.

(57)

ABSTRACT

The present disclosure includes a loose-cushion seat with improved lower-back support. At least one connector is applied to a loose-cushion seating unit that joins a portion of the peripheral surface of the seat cushion to a portion of the rear surface of the back cushion. The connector is removably attached to at least one of the seat cushion and the back cushion so the cushions can be detached from one another. The connector joins the cushions in such a manner that at least a portion the back cushion is pulled down to remain in close proximity with the top surface of the seat cushion when the seat cushion is depressed under the weight of a user, thereby providing improved lower-back support to the user.

10 Claims, 5 Drawing Sheets

